



PRIME Snowilent





SPECIAL FEATURES

- ❖ Ultra-high Efficiency, 80 PLUS® Titanium Certified (750 W)
- ❖ Super-High Efficiency, 80 PLUS® Platinum Certified (650 W)
- ❖ High Efficiency, 80 PLUS® Gold Certified (550 W)
- ❖ Fully Modular
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Premium Hybrid Fan Control
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ Super Low Ripple Noise [under 20 mV]
- ❖ Cable-free Connection Design
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ Multi-GPU Technology Support (750 W and 650 W)

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
750TR Titanium	20 A 100 W	20 A 100 W	62 A 744 W	0.3 A 3.6 W	3 A 15 W	750 W
650PD2 Platinum	20 A 100 W	20 A 100 W	54 A 648 W	0.3 A 3.6 W	3 A 15 W	650 W
550GD2 Gold	20 A 100 W	20 A 100 W	45 A 540 W	0.3 A 3.6 W	3 A 15 W	550 W



WIRE CONFIGURATION

Cable						
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
750TR Titanium	1	2	4	10	5	1
650PD2 Platinum	1	1	4	6	3	1
550GD2 Gold	1	1	2	6	3	1



12 YEARS WARRANTY



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 170 mm (L) x 150 mm (W) x 86 mm (H) (750 W)

Dimensions: 140 mm (L) x 150 mm (W) x 86 mm (H) (650 W, 550 W)



Specifications may change without prior notice



Headquarters sales@seasonic.com
 USA ssa.sales@seasonic.com
 Europe sse.sales@seasonic.com